



# ARKYX-SATÍN®

TECHNICAL DATA ARKYX-SATÍN®

## DESCRIPTION AND CHARACTERISTICS

**Arkyx- Satín®** is a product specially formulated to modify the concrete appearance with blended tones depending on your own election, personality and choices. When applying on concrete floor such: stamped floors, mortars, troweled floors, either in exteriors or interiors floors; we obtain special effects on floors and walls. Handling our miscellany of colors getting an elegant- unique appearance. Bearing in mind that the result applying the product varies depending on the quality and constructive conditions and the concrete age.

## APLICACION AND USE

- ◇ On new concrete floors, surface must have at least with 28 days curing, so the dry process ends. Then apply **Arkyx- Satín®**.
- ◇ When using **Arkyx-Satín®** can be applied at 100% or mixed up with clean water in a rate of 1:1. Depending on the result you are looking for, you are able to search your own proportion. If you aren't applying at 100%, it'd apply in layers, the first one in a rate of 1:. If needed; a second or more layer could be applied to get an appearance with satin background. The more water is added the tone will be lighter and more varigated. Using it directly the tone will be more intense.
- ◇ EsIt's needed to prepare the precise amount of **Arkyx-Satín®** to utilize. Use product of the same lot avoiding to add other components. Take note of the proportions made, to keep the same tonality if needed goa head. Take samples before applying it.
- ◇ Prior to apply **Arkyx-Satín®** the area should be clean , free of dust, grease, oil, spots, residues of curing agents. If the surface is damaged like older floors, the reaction of the product could be different since this material does not correct imperfections in the finish work. Ask for the **Arkyx-Satín®** cleanness line. Don't use muriatic acid, detergents, chlorine, solvents or similar products.
- ◇ Wearing glasses, particle mask, gloves and boots knee; shake well the container before applying; depending or the mixed up with water in a 1:1 ratio into a plastic nozzle pump sprayer-similar to fumigating equipment, taking samples you are able to get your own proportion.





# ARKYX-SATÍN®

TECHNICAL DATA ARKYX-SATÍN®

◇ Use brush for details. Let **Arkyx-Satin®** acting for 24 hours, protect the job area to avoid unwanted footprints. Then you should neutralize the surface to deactivate the acid components with one ¼ of **Neutro-Clean Arkyx®** mixed up with 1 up 2 buckets of clean water. Wash out in a no more of 10 minutes lapse. Use a rubber floor squeegee-avoid to scrub-to distribute and draw the water excess with a vacuum cleaner or traditional methods. Let the surface dry out completely to apply the **Sealer-Varnish Arkyx® Urethane**, to obtain an aesthetic and elegant finished job since the color is lifted up. Apply it over surfaces completely dry and clean. The curing time depends on climate factors and environment temperature-see technical data: **Varnish-Sealer Arkyx® Urethane**.

## RECOMMENDATIONS

Avoid applying under extreme climates like rain or winds. Always try to have ventilated and protected around the job area. Bear in mind all of the time specially in blue and green colors you must not wash the floor. Let dry out completely and apply the **Sealer-Varnish Arkyx® Urethane**. Take samples before applying it. NOT RECOMMENDED FOR BELIC OR INDUSTRIAL MACHINERY.

Featuring	Covering	Mixed up 1:1 with water
Gallon (Gall.)	200 sqf (=20m2)	400sqf (=40m2)
Liter (Lt.)	50sqf (=5m2)	100sqf (=10m2)



*\*Coverage and tones are approximated to the King of materials absorption and the way of application.*

*\*For special request and quotes visit your distributor site [www.arkyx.com](http://www.arkyx.com)*





# ARKYX-SATÍN®

TECHNICAL DATA ARKYX-SATÍN®

## MANAGMENT, STORAGE, CAUTION AND SECURITY

It's important protect the product of not ordinary climates, keeping it in a close place and well ubicada, avoiding bad diligences and attention for longer container and product duration. Thus, it's useful life endures more than 13 months if the product remains in the original container with the unsealed lid. Do not manipulate this product with extra components to avoid its good use, for that; you should know the concrete floor historical to ensure and succesful and good use of this product.

The quality of our products is supervisated in respect of it's distribution an election of the different colors, it's very important follow the instructions to carry out an final and hopefully finish job. If you don't keep it the results could vary over the surface even with the kind of cemento r the actual concrete floor.

## INFORMATION AND RECOMMENDATION

\*Use work clothes for application and protection of eyes, hands and other members, do not leave within reach of children, in case of eye contact rinse thoroughly with water and seek medical attention. \*All material is inspected before embarkation, the manufacturer **ARKYX®** is not responsible for expenses that arise in the installation, sale or resale, time and use of the product, freight charges, shipping and will be at the risk and expense of Buyer, each recommendation made by the manufacturer is based on own research and experiences that are emerging in areas of work in general.



# HDS

# ARKYX-SATÍN®

TECHNICAL DATA ARKYX-SATÍN®

FTAS060717I

## TECHNICAL DATA

\*It's important to apply with brush or sprayer over a surface 100% dry and clean.

\*Straight from the container 1 gallon covers about 200 sqf (=20m2)

\*Aspect : corrosive liquid

\*Mixed with water: Excellent

\*Flammable: No

\*Featuring: Gallon, liter

\*Finish: Oxidated Satin

\*Conventional Colors: Ocre Elegant, Pebble Stone, Dessert Ambar, Black Liverpool, Lagoon Green, Blue Satín y Purple Satín. (See more in: Catalogue Arkyx Satín® [www.arkyx.com](http://www.arkyx.com))

## CAUTION

Keep out of reach of children. Protect this product from moisture. Rinse your hands before and after using the product.

Use masks and avoid contact with eyes, using lenses, if this happens wash with plenty of water for 20 minutes.

And consult your doctor immediately.



*100% under the responsibility of the buyer the turn or use of the product, for their own needs and tastes.*

## ARKYX® SYSTEMS

Bldv. Solidaridad #700 Local No.15 between Tepic y Camelia Col. Libertad C.P. 83130

Hermosillo Sonora, México. Tel.:(662)2186462 [ventas@arkyx.com](mailto:ventas@arkyx.com) | [www.arkyx.com](http://www.arkyx.com)



Arkyx-Satín® | p. 4/6





# ARKYX-SATÍN® Catalogue



*\*Approximate Colors*





# ARKYX-SATÍN® Catalogue



*\*Approximate Colors*

## ARKYX® SYSTEMS

Blvd. Solidaridad #700 Local No.15 between Tepic y Camelia Col. Libertad C.P. 83130  
Hermosillo Sonora, México. Tel.:(662)2186462 [ventas@arkyx.com](mailto:ventas@arkyx.com) | [www.arkyx.com](http://www.arkyx.com)

