

DESCRIPTION AND CHARACTERISTICS

Arkyx- Satín® Is a product based of friendly enviroment components, such products applied over whether concrete floors or concrete stamped floors, we obtain special effects with diferent colors, giving a variety of tonalities. Taking advice that the result in the product application varies depends on the constructive condition and how old the floor is. Offering a decorative appearance in outside and inside, don't have an effect to the environment with odors and chemical reactions, its oxidation time is quick and effective, that is, you don't have to neutralize or wait a long penetrating time. Special for applying over new and existing concrete floors such smooth concrete floors and stamped concrete floors or over any kind of concrete surface. We encourage to test samples prior to the application to check the tone and reaction. The colors impregnation reacts at his maximun coloration, offering a resembling appearance to the stain concrete based acid (See Bío-Satín Colors Catalogue). Also, it's important using the Urethano Sealer Varnish Arkyx for final finishing, enhancing and protecting the stained base.

APLICACION AND USE

- ◇ Before applying surfaces must be clean, dust free, no oils or grease and dry. Shake the product before applying, then pour a portion directly from the original container to a sprayer pump, set the nozzle at breeze mode, applying with circular movements, also, you could apply it using brush for details and paint roll depending on the finish.

IN CASE OF PERFORMING THE NEXT FINISHINGS

Case 1. Over coating: If several lays apply are required it's recommended start with a light to more intense color, waiting till the first coat be quite, dry to begin with the second coating and so on, up to coming to the finish wished. Take samples first.

Case 2. Finished marble: Apply the product straight over the surface extending it using a floor squeegee to cover completely the work area, to disappear the marked lines spray lightly with water over the surface to get a mottled effect.



- ◇ After 24 hrs, proceed with the **Sealer-Varnish Arkyx® Urethane** application, over a clean and completely dry surface to get an elegant and aesthetic finished work.

RECOMMENDATIONS

Surface can be lightly spreaded with clean water to get more penetration in the concrete. Apply over dry surfaces ovoiding puddles. This product is water-based, hence; it can be mixed up to 1:1 with clean water to reach changes on the tone intensity. Avoid to apply the **Sealer-Varnish Arkyx® Urethane** under wet climates, This product doesn't hide cracks. Take samples before applying it. NOT RECOMMENDED FOR BELIC OR INDUSTRIAL MACHINERY.

Featuring	Covering	Mixed up 1:1 with water
Gallon (Gall.)	200 sqf (=20m2)	400sqf (=40m2)
Liter (Lt.)	50sqf (=5m2)	100sqf (=10m2)



**Coverage and tones are aproximated to the King of materials absortion and the way of application.*

**For special request and quotes visit your distributor site www.arkyx.com*



MANAGMENT, STORAGE, CAUTION AND SECURITY

It's important protect the product of not ordinary climates, keeping it in a close place and well ubicada, avoiding bad diligences and attention for longer container and product duration. Thus, it's useful life endures more than 13 months if the product remains in the original container with the unsealed lid. Do not manipulate this product with extra components to avoid its good use, for that; you should know the concrete floor historical to ensure and succesful and good use of this product.

The quality of our products is supervisated in respect of it's distribution an election of the different colors, it's very important follow the instructions to carry out an final and hopefully finish job. If you don't keep it the results could vary over the surface even with the kind of cemento r the actual concrete floor.

INFORMATION AND RECOMMENDATION

*Use work clothes for application and protection of eyes, hands and other members, do not leave within reach of children, in case of eye contact rinse thoroughly with water and seek medical attention. *All material is inspected before embarkation, the manufacturer **ARKYX®** is not responsible for expenses that arise in the installation, sale or resale, time and use of the product, freight charges, shipping and will be at the risk and expense of Buyer, each recommendation made by the manufacturer is based on own research and experiences that are emerging in areas of work in general.

HDS

BÍO-SATÍN®

TECHNICAL DATA BÍO-SATÍN®

FTBS161017I

TECHNICAL DATA

*It's important to apply with brush or sprayer over a surface 100% dry and clean.

*Straight from the container 1 gallon covers about 200 sqf (=20m2)

*Aspect : corrosive liquid

*Mixed with water: Excellent

*Flammable: No

*Featuring: Gallon, liter

*Finish: Oxidated Satin

*Conventional Colors: Ocre Elegant, Pebble Stone, Dessert Ambar, Black Liverpool, Lagoon Green, Blue Satín y Purple Satín. (See more in: Catalogue Arkyx Satín® www.arkyx.com)

CAUTION

Keep out of reach of children. Protect this product from moisture. Rinse your hands before and after using the product.

Use masks and avoid contact with eyes, using lenses, if this happens wash with plenty of water for 20 minutes.

And consult your doctor immediately.



100% under the responsibility of the buyer the turn or use of the product, for their own needs and tastes.

ARKYX® SYSTEMS

Bldv. Solidaridad #700 Local No.15 between Tepic y Camelia Col. Libertad C.P. 83130

Hermosillo Sonora, México. Tel.:(662)2186462 ventas@arkyx.com | www.arkyx.com

