

## DESCRIPTION AND CHARACTERISTICS

**Neutro-Clean®** It is important that all floors and surfaces, specially satin floors (oxidating floors), es-tamped floors, quarry Stone, slab Stone, mosaics, vitropisos, porous floors, require preventive an unexpensive cleanness. It has to be efective and to offer a nitid surface, free of álcalis and sulfates that water contains. So dust and ordinary filth.

The Neutralizer is used to:

- ◇ Cleaning concrete surfaces or derivatives as maintenance.
- ◇ Washing of the surface after the application of the oxide with Satin-Arkyx® in order to neutrali-ze the same acid, encapsulating it so that it does not continue working in the slab.
- ◇ Cleaning to avoid residues of scale due to the water used for cleaning. Then the application of the Varnish Sealer Arkyx® can be continued.

## APLICACION AND USE

- ◇ **Satin Stained Floors:** a) One day after of the proceder, mix up a quarter of liter(1/4 gal) of Neutro-Clean® in a 19lt (4gal) bucket. Then pour out on the floor extending it with floor squeegee or brush. Repeat this, procedure as necessary to cover the total area to clean. Then rinse with water until the surface were enought clean. Wait at least 3 days so the area be quite dry to apply Varnish-Sealer Uret-hane Arkyx® for daily maintenance use oil for Shiny floor® , as much as you consider is requarred. Do not leave more than 10 minutes.
- ◇ **Stamped Concrete Floors:** One day after the stamped, remove the releaser powder with ware house broom, deposit it into disposable bags. Then follow the same process for Satin Stained Floors as des-cribed above in step a).



## MANAGEMENT, STORAGE, CAUTION AND SECURITY

It's important to protect the product from not ordinary climates, keeping it in a cool place and well located, avoiding bad diligences and attention for longer container and product duration. Thus, its useful life endures more than 13 months if the product remains in the original container with the unsealed lid. Do not manipulate this product with extra components to avoid its good use, for that; you should know the concrete floor history to ensure and successful and good use of this product.

The quality of our products is supervised in respect of its distribution and election of the different colors, it's very important to follow the instructions to carry out a final and hopefully finish job. If you don't keep it the results could vary over the surface even with the kind of cement or the actual concrete floor.

## INFORMATION AND RECOMMENDATION

\*Use work clothes for application and protection of eyes, hands and other members, do not leave within reach of children, in case of eye contact rinse thoroughly with water and seek medical attention. \*All material is inspected before embarkation, the manufacturer **ARKYX®** is not responsible for expenses that arise in the installation, sale or resale, time and use of the product, freight charges, shipping and will be at the risk and expense of Buyer, each recommendation made by the manufacturer is based on own research and experiences that are emerging in areas of work in general.



# HDS

# NEUTRO-CLEAN®

TECHNICAL DATA NEUTRO CLEAN ARKYX®

FTNC020817I

## TECHNICAL DATA

\*Straight from the container 1/4 de Liter is mixed for a bucket (19lt) of water, covers about 20sqf(=20m2)

\*Physical State: Líquid / Odor: Any / Toxicity: Any

\*Mixed in water: Yes

\*Flammable: No

\*Featuring: Quarter liter, liter y gallon

\*Color: Semi transparent

Properties:% Total purity as NaHCO<sub>3</sub> 99.0 - 101.0% NaHCO<sub>3</sub> 93.0 - 99.0% Na<sub>2</sub>CO<sub>3</sub> residual Less than 4.0. The PH of a solution of 5.0 g in 100 ml of water must be less than 8.6 Losses on drying Maximum 0.25% Chlorides Maximum 0.015% Sulfur expressed as Sulphates Maximum 0.015% Iron Maximum 5 ppm Aluminum Maximum 2 ppm Arsenic Maximum 2 ppm Heavy metals Maximum 2 ppm Presence of ammonia Negative

## CAUTION

Keep out of reach of children. Protect this product from moisture. Rinse your hands before and after using the product.

Use masks and avoid contact with eyes, using lenses, if this happens wash with plenty of water for 20 minutes.

And consult your doctor immediately.



*Queda al 100% bajo la responsabilidad del comprador el giro o uso del producto, para sus propias necesidades y gustos.*

## SISTEMAS ARKYX®

Solidaridad #700 Local No.15 entre Tepic y Camelia Col. Libertad C.P. 83130

Hermosillo Sonora, México. Tel.:(662)2186462 [ventas@arkyx.com](mailto:ventas@arkyx.com) | [www.arkyx.com](http://www.arkyx.com)



PisosEstampadosArkyx

Neutro-Clean® | p. 3/3

