



ACRYLIC SEALER VARNISH ARKYX®

DATE SHEET ACRYLIC SEALER VARNISH ARKYX®

DESCRIPTION AND CHARACTERISTICS

Acrylic Sealer Varnish Arkyx® Is an acrylic resins covering that let a semi-brilliant surface, solvents based. Designed technically and aesthetically for surfaces on floors and walls, moreover offers salts resistance, acids, ultraviolet rays and abrasives elements protection. This is a polymer sealer unique for exterior and interior, protecting floors and walls surfaces adding a special aesthetics.

USES AND APPLICATION

Perfectly applicable by its transparency, allows seal and brightness any surface on stamped floors concrete based, troweled, broomed, roof tiles, washed Stone floors, flag Stone, and decorative elements. Flagstone walls, brick and block walls, common finisher on plastering and texturized either colored or not.

Acrylic Sealer Varnish Arkyx® is packed and ready to apply, you don't need thin it up with any kind of solvent.

Prior to apply **Acrylic Sealer Varnish Arkyx®**, the area must be cleaned and completely dry, free of dust, grease, oil, stains, free of particles bad added and alterations. For this product won't fix finished imperfections.

Must be applied after the next three or four days of washed and of course the area should be free of humidity.

Shake the container before use it, easy to apply with paint roller, spray nozzle, use paint brush for details.

It dries to the touch time in 5.0 up to 8.0 hours under normal conditions, for traffic use must wait till 48 hours, under 30°-40°C (86°F-104°F) more or less.

(the time mentioned above depends on the weather and local temperatura).





ACRYLIC SEALER VARNISH ARKYX®

DATE SHEET ACRYLIC SEALER VARNISH ARKYX®

ADVANTAGES

Excelent and aesthetic finished, ease to apply, ready to use, it doesn't need any combination, transparent featuring, if color needed, just add Arkyx® pigments according the tone intensity required.

RECOMMENDATIONS

Avoid to apply under extreme sunny weathers, windy and rainy environments. In interiors keep the area ventilated and protect the covering area, broom the area before apply it, if necessary; use an empty, dry and clean bucket to ease the work appication. You can use any **Acrylic Sealer Varnish Arkyx®** as maintenance agent. We recommend taking a sample before the application.

| Featuring | Covering |
|----------------|----------|
| 1/4 Liter | 0.8-1m2 |
| Gallon (Gall.) | 18-20m2 |
| Liter (Lt.) | 3-5m2 |
| Bucket (18Lt.) | 80-100m2 |



**Coverage and tones are aproximated to the King of materials absortion and the way of application.*

**For special request and quotes visit your distributor site www.arkyx.com*





ACRYLIC SEALER VARNISH ARKYX®

DATE SHEET ACRYLIC SEALER VARNISH ARKYX®

MANAGEMENT, STORAGE, CAUTION AND SECURITY

It's important to protect the product from not ordinary climates, keeping it in a close place and well located, avoiding bad diligences and attention for longer container and product duration. Thus, its useful life endures more than 13 months if the product remains in the original container with the unsealed lid. Do not manipulate this product with extra components to avoid its good use, for that; you should know the concrete floor historical to ensure and successful and good use of this product.

The quality of our products is supervised in respect of its distribution and selection of the different colors, it's very important to follow the instructions to carry out a final and hopefully finish job. If you don't keep it the results could vary over the surface even with the kind of cement or the actual concrete floor.

INFORMATION AND RECOMMENDATION

*Use work clothes for application and protection of eyes, hands and other members, do not leave within reach of children, in case of eye contact rinse thoroughly with water and seek medical attention. *All material is inspected before embarkation, the manufacturer ARKYX® is not responsible for expenses that arise in the installation, sale or resale, time and use of the product, freight charges, shipping and will be at the risk and expense of Buyer, each recommendation made by the manufacturer is based on own research and experiences that are emerging in areas of work in general.





HDS

ACRYLIC SEALER VARNISH ARKYX®

FTBSA120717E

THECNICAL DATA

*It's important to apply with brush or air sprayer over 100% dry and clean surface.

*Direct from the container at one hand covers about from 1 up to 1.25m2 per liter (=10 sf up to 12 sf), according to the surface rugosity and absorption capacity. ASTM NORMS.

*Featuring: Liquid

*Abrasive resistance: Up to 100% higher than the normal concrete

*Mixed with water: No

*Flammable: Yes

*Presentation: the comercial units are, ¼ lt, 1lt, 1 gll.(3.78lts.), 1 bucket(18 lts.), 1 barrel(174 lt).

*Color: Transparent

*Finished: Wet and semi-shiny appearence.

*Casos: "burbujas" ,"curado rápido" : exceso de des gasificado de la superficie por temperaturas elevadas en superficies, mezclado excesivo con aire. "curado lento": mezclado deficiente, temperaturas muy bajas en superficies, uso de solventes en mezcla, capas muy delgadas por uso excesivo de solvente, uso de diluyentes en producto, condiciones climáticas extremas durante aplicación y durante secado que se reflejan al tiempo, casos anteriores también puede producir descaramientos, descaramientos entre capas, amarillamiento, ojos de pescado, a causa de contaminación de aceites, mala limpieza de superficie, residuos de desmoldantes, mezclado deficiente, humedad antes y después de aplicación, antes de secado, etc. Favor de realizar las recomendaciones de aplicación.

CAUTION

Keep out of reach of children. Protect this product from moisture. Rinse your hands before and after using the product.

Use masks and avoid contact with eyes, using lenses, if this happens wash with plenty of water for 20 minutes.

And consult your doctor immediately.



100% under the responsibility of the buyer the turn or use of the product, for their own needs and tastes.

ARKYX® SYSTEMS Blvd. Solidaridad #700 Local No.15 between Tepic y Camelia Col. Libertad C.P. 83130
Hermosillo Sonora, México. Tel.:(662)2186462 ventas@arkyx.com | www.arkyx.com



PisosEstampadosArkylx

